

## FITTING THE HARNESS:

1. Loosen straps from the adjustable 3-bar buckle.
2. Open harness and lay flat with the logo facing the floor. Have your dog step into the harness so his front legs are in the openings and the size tag is facing forward. Pull harness up and around your dog's chest. Close the buckle (**fig. 1**), making sure the D-Rings are towards your dog's tail.
3. Tighten the two front straps for a firm fit. Make sure both front straps are equal length. (**fig. 2**) Repeat adjustment for rear straps.

**CAUTION:** Do not over-tighten straps. When correctly fitted, harness should be snug but allow two fingers to fit easily between the straps and your pet. (**fig. 3**)

4. Insert the strap under the adjustable 3-bar buckle. (**fig. 4**)
5. Insert the strap through the opening on the hook & loop keeper. (**fig. 5**) Move the keeper next to the 3-bar buckle. Fold excess strap and secure in keeper with hook & loop tabs. (**fig. 6**) Repeat steps 4 & 5 with the other straps.

## SECURING YOUR DOG IN THE CAR:

1. Secure the locking buckle with the red slider tab. (**fig. 7**)
2. Place your pet comfortably on the rear seat of your vehicle. Thread the seatbelt through both handles of the harness (**fig. 8**) and click into the seatbelt buckle. Tighten the seatbelt.

## USE AS A WALKING HARNESS:

1. Clip your leash through both D-rings at the back of the harness. (**fig. 9**)



fig. 1



fig. 2



fig. 3



fig. 4



fig. 5



fig. 6



fig. 7



fig. 8



fig. 9