



_				
ΗП	no	۱Ťſ	OI	15
		,	Ο.	. •

- Easy and labour-saving attachment to the towbar with leverless, patented IQ quick-release fastener
- Patented, removable spacers with single-hand operation
- New extra-wide wheel rails for tyre widths up to 4.5 inches
- Foldable wheel rail and lamp unit
- Ratchet system for securely attaching the wheels to the wheel rail
- At only 20 kg, it's particularly light and, thanks to this low dead weight, allows for a large payload without additional rigging
- Convenient release of the folding function with foot lever
- Quick-release lever for fixing the wide carrier frame
- Anti-theft device with simultaneous locking
- Quality product made in Germany with 3-year warranty

Technical details				
Number of bikes	4			
Dimensions (mounted)	119 x 73 x 91 cm (WxHxD)			
Dimensions (folded)	61 x 23 x 91 cm (WxHxD)			
Weight	20 kg			
Wheel rail distance	19/18/18 cm			
Payload (support load ≥ 75 kg)	max. 55 kg			
Payload (support load ≥ 80 kg)	max. 60 kg			
Max. bike centre distance	130 cm			
Folding angle	90°			
Minimum requirements of the towbar				
Material quality	min. St 52-3			
Support load	min. 75 kg			
Diameter of towbar neck	min. Ø 28.5 mm			



REMOVABL SPACERS

MAX. 60 KI PAYLOAD



20 KG DEAD WEIGHT



90° FOLDING FUNCTION



SMALL FOLDING SIZE



EXTRA EASY ASSEMBLY



WITHOUT TOOL



ANTI-THEFT



FOR E-BIKES

Accessories:

Transport and storage bag Art. 25040





Drive-on and drive-over ramp (foldable) Art. 19950



