



Spark 3
Technical specifications

760mm Distance from centre of tow ball




800mm

Height of upright frame

180mm 180mm 210mm Distance from centre of tow ball to centre Distance of first wheel tray.
between bikes

Max distance from centre of tow ball



300mm

Tilt range from the centre of the tow ball

250mm Height from the tow ball housing

Width folded 960mm

Depth folded 910mm



Height folded 310mm







Make - BUZZRACK

Model - Spark 3

Type - Tow ball mount

Colour / finish - Silver

Weight- 17.1kg

Max load weight exc carrier - 55kg

Tilt or slide - Tilts away from vehicle

Max number of bikes - 3

Fits bolt on tow balls - Yes

Fits swan neck or detachable tow balls - Yes

Min wheelbase - 510mm

Max wheelbase - 1190mm

Length of wheel straps - 392mm

Bike to carrier lock - Yes

Carrier to vehicle lock - Yes

Integral lighting board - Yes

Fits with spare wheel - No

Possible to tow when in use - No

Available accessories - Buzz cable lock, buzz loading ramp, long wheel strap (492mm)

Length of guarantee - 3 years

Suitable for - Electric bikes, fat bikes (adapter available separately)

Important information - The maximum permitted load you can carry is also determined by your nose weight; you will need to check you don't exceed this before using any tow ball mounted bike carrier.

Requires 65mm clearance from the centre of tow ball to the rear of the vehicle.

